

Product information

» Product facts material Storeroom

Product	Dimensions (mm)	Additional information
F		
Panel (frame)	Verticals 19,0 x 19,0 x 1,0	
	Horizontals 15,0 x 15,0 x 1,0	
Wire	Verticals \varnothing 3,0	
	Horizontals \varnothing 2,5	
	Mesh Apertures 50 x 65	
Door (frame)	Uprights 30,0 x 20,0 x 1,5	
	Horizontals 25,0 x 15,0 x 1,5	
Colour	RAL9018	
FK		
Panel (frame)	Uprights 30,0 x 20,0 x 1,5	
	Horizontals 25,0 x 15,0 x 1,5	
Wire	Vertical \varnothing 4,0	
	Horizontal \varnothing 4,0	
	Mesh Apertures 50 x 65	
Door (frame)	Verticals 30,0 x 20,0 x 1,5	
	Horizontals 25,0 x 15,0 x 1,5	
Colour	RAL9018	
FK+		
Panel (frame)	Uprights 30,0 x 20,0 x 1,5	Strengthened
	Horizontals 25,0 x 15,0 x 1,5	
Wire	Vertical \varnothing 5,0	
	Horizontal \varnothing 5,0	
	Mesh Apertures 50 x 65	
Door (frame)	Verticals 40,0 x 20,0 x 1,5	Strengthened
	Horizontals 35,0 x 15,0 x 1,5	
Colour	RAL9018	
FP		
Panel (Profiled Sheet Metal)	Deep of profile 30,0	
	Thickness of sheet 0,7	
Colour	Sendzimir	
Door (Sheet Metal)	Uprights 30,0 x 20,0 x 1,5	
	Horizontals 25,0 x 15,0 x 1,5	
	Thickness of sheet 0,7	
Colour	RAL9018	
Lower attach for panel		U-Profile
		(F=19 x 19; FK/ FP=30 x 20)
Upper mount for panel		Ceiling fitting
		Sheet Metal 2 mm
Shelves		Made by blockboard (Birch/ Al)
		Brackets included

Product information

» Product facts material Storeroom

Storeroom walls Operating and maintenance instructions

Cleaning: *To clean, use water and a soft detergent. Excess water can be wiped off with a cloth. Scouring, wire brush, scouring pad or other products of abrasive may not be used.*

OPERATING AND MAINTENANCE INSTRUCTIONS					
CLEANING	ARE MADE X TIMES PER			IN CASE	ANNEX
	WEEK	MONTH	YEAR		
				X	

Improvement of the color can be made if necessary. Extra spray paint can be purchased by Axelent AB.

NOTE! Axelent storeroom walls must not be stored outdoors or in moist environments where the risk of corrosion is present.